

iNFINITY

N

DMxxxG12T-B66HSW
695~720W

23.2%

15

30

• 40
• ESG
100%

ESG



(LCOE (BOS



TÜV



SA 8000
ISO 9001
ISO 14001
ISO 45001
ISO 50001
ISO 27001

IEC 61215, IEC 61730
(IEC TS 63209
(IEC 62716
(IEC 61701
(IEC 60068
LeTID (IEC TS 63342)

99%


87.4%



DMxxxG12T-B66HSW



N	132 (6×22)
(mm)	2384x1303x33
(kg)	37.7
2mm	镀膜
2mm	
3	IP68
输出线缆 (含连接器)	4mm²/ : 360mm(+)/200mm(-) : 1400mm(+)/1400mm(-)
PV-ZH202B	MC4-EVO 2A (1500V)



(mm)



1

DM695G12T-B66HSW DM700G12T-B66HSW DM705G12T-B66HSW DM710G12T-B66HSW DM715G12T-B66HSW DM720G12T-B66HSW

(Pmax/W)
(Imp/A)
(Vmp/V)
(Isc/A)
(Voc/V)
STC (%)

¹ IEC 60904-3 : : ±4% : ±3% : ±3% : 80%±5%
² STC (): 1000W/m² 25 AM=1.5
³ NMOT: 800W/m² 20 AM=1.5 1m/s



1 (BNPI²)

(W	695	700	705	710	715	720
(Pmax/W)						
(Imp/A)						
(Vmp/V)						
(Isc/A)						
(Voc/V)						

¹ IEC 60904-3 : : ±4% : ±3% : ±3%
² BNPI: 1000W/m² 135W/m² 25 AM=1.5



()
(V)
(A)
(%)
(Pa)
(Pa)



(NMOT)
Pmax (%/)
Voc (%/)
Isc (%/)



	17.5m
<i>l</i> (mm)	2440x1140x1420
<i>l</i>	33
<i>l</i>	759

